



ALL SAFINTRA ROOF SYSTEMS WILL ONLY BE WARRANTED IF INSTALLED WITH SAFINTRA-APPROVED FASTENERS






How to read our fastener sizes		
Gauge <div style="border: 1px solid black; padding: 2px; width: 100px; margin: 5px auto;">12</div> (Diameter of shank excluding thread) #8 - 4.2mm #10 - 4.8mm #12 - 5.5mm #14 - 6.3mm	Threads Per Inch <div style="border: 1px solid black; padding: 2px; width: 100px; margin: 5px auto;">14</div> Number of thread crests that can be counted along a lineal measurement of 1 inch. (TPI).	Length <div style="border: 1px solid black; padding: 2px; width: 100px; margin: 5px auto;">75mm</div> Overall length of shank including drill point, up to shank beneath head.
		

ALL FIXTITE FASTENERS CARRY A MANUFACTURER'S WARRANTY AND COMPLY WITH SANS1273-2009 (AS3566.2-2002) STANDARDS



- All Safintra Fixtite™ fasteners provide optimal service life with Safintra's range of products.
- Different lengths/types of fasteners are available on request, including stainless steel.
- For optimal performance, the service life warranty of fasteners must match the service life warranty of the sheeting.
- Only Class 3 (concealed fix) and Class 4 fasteners are suitable for use with aluminium-zinc coated steel (unpainted or pre-painted).
- Class 4 fasteners must be used within 1km of the coast, rivers and in all corrosive environments.
- Only use stainless steel fasteners for aluminium sheeting.

FIXTITE™ FASTENER APPLICATION GUIDE

METAL APPLICATIONS

#10 x 22mm Metalfix wafer head square drive
For concealed fix onto metal (Saflok 700, Saflok 410 & Newlok) Class 4
Code: FN0400 
#12 x 65mm Metalfix hex head washer flange, EPDM seal
For trapezoidal onto metal (Tufdek IBR, Widedek, Fluteline, Trimflute) Class 4
Code: FN0409 
#12 x 38mm Metalfix hex head washer flange, EPDM seal
For pierced fix onto metal (Classicorr Corrugated) Class 4
Code: FN0407 
#14 x 22mm Metalfix stitching screw, hex washer flange, EPDM seal, tapered
For stitching of sheeting & flashings, and use with S-5 clamps Class 4
Code: FN0412 
#12 x 25mm Metalfix hex head washer flange, EPDM seal
For side cladding onto metal Class 4
Code: FN0413 

TIMBER APPLICATIONS

#10 x 45mm Timberfix wafer head square drive
For concealed fix onto timber (Saflok 700, Saflok 410 & Newlok) Class 4
Code: FN0401 
#12 x 85mm Timberfix hex head washer flange, EPDM seal
For trapezoidal onto timber (Tufdek IBR, Widedek, Fluteline, Trimflute) Class 4
Code: FN0411 
#12 x 65mm Timberfix hex head washer flange, EPDM seal
For pierced fix onto timber (Classicorr Corrugated) Class 4
Code: FN0410 